


LED Treiber 100W 24V Stecksytem

A white, rectangular electronic LED converter. It has a power cord with a two-prong electrical plug on the left. On the right side, there is a multi-pin connector with four gold-colored pins. The top surface of the device is printed with the following text: "Hera LED 24/100W", "Electronic LED converter", "Prim. = 230-240V ~ 50-60 Hz $\lambda = 0.95$ ", "Sec. = 24V DC max. 4.17A 100W", "Ta 50°C Tc 80°C", and various safety and certification symbols including CE, a triangle with a dot, a triangle with an exclamation mark, a triangle with a lightning bolt, a triangle with a circle, and a triangle with a cross. The bottom of the device has two mounting holes.

| | 1 A | 15 A | 20 A | 40 A | 50 A | 100 A | 120 A | 200 A |
|--------------------------|-----------------------------------|---------|--------|--------|--------|--------|--------|-------|
| Leuchtdichte (cd) | 21 mm | 16,1 mm | 21 mm | 30 mm | 30 mm | 30 mm | 30 mm | 30 mm |
| Unterbrechung (s) | Reihe der Zeitschalter (s) | | | | | | | |
| • 41 mm | 40 mm | - | - | - | - | - | - | - |
| • 43 mm | 25 mm | 55 mm | 110 mm | 130 mm | - | - | - | - |
| • 44 mm | 20 mm | 25 mm | 50 mm | 100 mm | 100 mm | 100 mm | 100 mm | - |
| • 50 mm | 20 mm | 25 mm | 50 mm | 60 mm | 60 mm | 60 mm | 60 mm | 60 mm |

LED Treiber 100W, 24Vdc für Stecksystem. Elektronischer Sicherheitstransformator 24V DC, IP20, Netzanschlussleitung 2m mit Eurostecker, 12-fach Verteiler, max. zulässige Länge der Sekundärleitungen 5m. Maße: 185x60x31mm